



- Universally applicable Full HD IP camera with low-light technology, day / night - functionality
- Crystal-clear images in all safe, industrial areas
- Ensuring optimum control options with clearly visible people and processes
- Plug & play installation
- Power over Ethernet operation (PoE+)
- Electropolished stainless steel (SS316L) enclosure

A9

WebCode **IC930AFZA**



As a universally applicable Full HD IP camera with low-light technology, the IC-930 provides crystal-clear images in all safe, industrial areas - from food factories and pharmaceutical or chemical factories to ships and piers. The enclosure consists of AISI316L stainless steel.

The high degree of light sensitivity and the camera's day / night mode ensure brilliant images even in bad, low light. This ensures optimum control options with clearly visible people and processes.

Even the 30x zoom still provides optimum images and video streams with a frame rate of 60 images per second.

The camera can be operated in temperatures ranging from -40 °C to +65 °C and has IP66 / IP67 / IP68 as well as IP69. As a standard, the camera is supplied with supports for wall, ceiling and parapet mounting and with a sunshield. Another version is available with a wiper and an optional water tank.

Selection Table

Focus	Auto, manual, trigger		
Zoom	30x optical		
Viewing angle	61,6° (wide), 2,5° (tele)		
Network protocol	ONVIF Profile Q, S, T		
Interfaces	PoE+ (IEEE802.3at)		
Product Type	Integrated wiper	Art. No.	Weight kg
IC-930-AFZ-I30P00S2C10V2W00M00	No	271549	4.000
IC-930-AFZ-I30P00S2C10V2W01M00	Yes	271550	4.000

